

# D DISPENSERS

## RUM VISCOMAT

**EN.** Diesel transfer unit for non commercial use. Easily connected to drums via a quick 2" coupling. Fitted with a telescopic suction tube for direct connection to fuel drums and nozzle housing located above the drum, near the pump, for easy, clean operations. Fitted with mechanical meters to ensure precise dispensing and control of single user consumption.

**ES.** Grupo de trasiego de gasóleo para uso privado. Fácil de conectar al bidón mediante conexión rápida de 2". Se suministra con tubo telescópico en aspiración para conectar directamente al bidón y con alojamiento para la pistola situado en las proximidades de la bomba, sobre el bidón, para consentir un uso fácil y limpio del surtidor. Dispone de un cuentalitros mecánico que permite efectuar suministros precisos y administrar el consumo de los distintos usuarios.

**RU.** Узел перекачивания дизельного топлива для индивидуального пользования. Просто соединить с бочкой с помощью быстрого коннектора 2". Они оснащаются телескопической всасывающей трубой для непосредственного соединения с бочкой и гнездом для пистолета, что упрощает использование распределителя и позволяет избежать загрязнения. Они оснащены механическими счетчиками литров, которые обеспечивают точную подачу и позволяют контролировать потребление отдельных пользователей.

### PERFORMANCE

- AC and DC versions available
- Flow rate up to 25 l/min

- Disponible en versión CA y CC
- Caudal hasta 25 l/min

- Предлагаются модели с питанием от источника переменного и постоянного тока
- Расход до 25 л/мин

### PRODUCTS RANGE WEIGHT AND PACKAGING

Code	Weight		Packaging		
	kg	lbs	mm	inch	pcs/box
<b>F0026102D</b>	18	39,6	480x370x265	18,9x14,6x10,4	1
<b>F0026100D</b>	18	39,6	480x370x265	18,9x14,6x10,4	1
<b>F0026200D</b>	18	39,6	480x370x265	18,9x14,6x10,4	1
<b>F00268000</b>	9	19,8	357x357x275	14,1x14,1x10,8	1
<b>F00268010</b>	9	19,8	480x370x265	18,9x14,6x10,4	1
<b>000270000</b>	18	39,6	480x370x265	18,9x14,6x10,4	1
<b>000270010</b>	21	46,3	500x380x280	19,7x15x11	1



**Flow-rate**  
up to  
**25** l/min  
(up to 7 gpm)

**Accuracy**  
+/-  
**0,5 %**

**Viscosity**  
up to  
**2000** cSt



DC DRUM VISCOMAT



AC DRUM VISCOMAT

**FEATURES**



Ergonomic nozzle

(DC models)



Foot valve

(DC models)



Kit cable



Ergonomic nozzle

(AC models)



Extensible pipe

(AC models)



Mechanical meter

**ON REQUEST**

**PRODUCTS' RANGE TECHNICAL DATA**

Code	Description	Fluids type	Flow-rate		Voltage			Pump mod.	Nozzle type	Hoses lenght
			l/min	gpm	AC V./Hz DC Volt	Power Watt	Amp. max.			
F0026102D	DRUM Viscomat 200/2 110V/60HZ	☉	9	2	110	1500	15	Viscomat 200/2	Easyoil	4
F0026100D	DRUM Viscomat 200/2 230V/50-60HZ	☉	9	2	230-50/60	800/950	3,8/4,6	Viscomat 200/2	Easyoil	4
F0026200D	DRUM Viscomat 200/2 230V/50/60HZ K400	☉	9	2	230-50/60	800/950	3,8/4,6	Viscomat 200/2	K400	4
F00268000	DRUM Viscomat 60/1 12V	☉	4	1,2	12	150	18,5	Viscomat 60/1	Easyoil	4
F00268010	DRUM Viscomat 60/1 24V K400	☉	4	1,2	24	150	18,5	Viscomat 60/1	K400	4
000270000	DRUM Viscomat 70M	☉	28	7	230	750	4,6	Viscomat 70 M	Self3000	4
000270010	DRUM Viscomat 70M K33	☉	25	7	230	750	4,6	Viscomat 70 M	Self3000	4

The units can also be supplied for operating under different voltages and with meter.

SPENSERS

PUMPS

METERS

METERS  
NOZZLE

NOZZLE

EQUIPMENT/SPECIAL

MONITORING/FLUID

HOSEREEL

FILTERING

ACCESSORIES